



All dimensions are in millimetres.

MM Ø	A	B Ø	CH	H *	H	H1 max	D Ø	EE	KK	NA	WF	VE	Y ± 5	PJ** ± 5	ZJ**	V**
25	17	50	12	37	15	21	20	G 1/4	M 12×1,25	14	25	10	65	0	85	25
32	19	60	15	37	15	21	20	G 1/4	M 14×1,5	17	25	10	70	0	90	25
40	16	60	22	42	16	21	26	G 3/8	M 16×1,5	25	40	25	88	0	110	30
50	16	75	22	42	16	21	26	G 3/8	M 16×1,5	25	45	30	91	0	113	35
63	23	85	30	42	16	21	26	G 3/8	M 22×1,5	34	46	30	112	0	134	35
70	35	95	36	42	16	21	26	G 3/8	M 35×1,5	40	47	30	112	0	134	35
80	35	105	36	42	16	21	26	G 3/8	M 35×1,5	40	49	30	112	0	134	40
100	45	140	46	48	18	21	30	G 1/2	M 45×1,5	50	52	35	137	0	163	40
125	58	165	60	57	21	21	38	G 3/4	M 58×1,5	65	55	35	155	0	182	40
140	65	190	65	57	21	21	38	G 3/4	M 65×1,5	70	55	35	165	0	206	60

* Block valve can be mounted into the attachment.

** In strokes shorter than 50 mm, mounting dimensions ZJ and PJ shall lengthen by the length of the stroke - 50mm.

** In strokes exceeding 500 mm, mounting dimensions ZJ and PJ shall lengthen by the length V, due to additional piston rod guidance.

MM Ø	XO	L	CD Ø	EW	MR
25	101	16	12	12	16
32	110	20	16	16	20
40	148	38	20	20	25
50	158	45	25	25	27.5
63	185	51	30	30	32.5
70	185	51	30	30	32.5
80	203	69	40	40	50
100	251	88	50	50	61.5
125	282	100	60	60	70
140	321	115	70	70	82

