



All dimensions are in millimetres.

MM Ø	A	CH	H*	H	H1 max	D Ø	EE	KK	NA	WF	VE	Y ± 5	PJ** ± 5	ZJ**	V**
25	17	12	37	15	21	20	G 1/4	M 12x1.25	14	25	10	65	0	85	25
32	19	15	37	15	21	20	G 1/4	M 14x1.5	17	25	10	70	0	90	25
40	16	22	42	16	21	26	G 3/8	M 16x1.5	25	40	25	88	0	110	30
50	16	22	42	16	21	26	G 3/8	M 16x1.5	25	45	30	91	0	113	35
63	23	30	42	16	21	26	G 3/8	M 22x1.5	34	46	30	112	0	134	35
70	35	36	42	16	21	26	G 3/8	M 35x1.5	40	47	30	112	0	134	35
80	35	36	42	16	21	26	G 3/8	M 35x1.5	40	49	30	112	0	134	40
100	45	46	48	18	21	30	G 1/2	M 45x1.5	50	52	35	137	0	163	40
125	58	60	57	21	21	38	G 3/4	M 58x1.5	65	55	35	155	0	182	40
140	65	65	57	21	21	38	G 3/4	M 65x1.5	70	55	35	165	0	206	60

* Block valve can be mounted into the attachment.

** In strokes shorter than 50 mm, mounting dimensions ZJ and PJ shall lengthen by the length of the stroke - 50mm.

** In strokes exceeding 500 mm, mounting dimensions ZJ and PJ shall lengthen by the length V, due to additional piston rod guidance.

MM Ø	WC	VD	NF	BC Ø e8	FC	UC	FB	AA
25	28	3	14	65	85	104	11	50
32	28	3	17	75	95	118	11	60
40	43	3	17	75	95	118	11	60
50	48	3	22	90	115	138	13	75
63	49	3	25	100	125	158	13	85
70	50	3	27	115	145	178	17	95
80	52	3	27	125	155	188	17	105
100	55	3	35	165	205	245	21	140
125	58	3	40	225	275	335	30	180
140	58	3	40	225	275	335	30	190

